

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
2 August 2001 (02.08.2001)

PCT

(10) International Publication Number
WO 01/54621 A1

(51) International Patent Classification⁷: A61F 2/06

55369 (US). HAVERKOST, Patrick, A.; 6730 Toledo Avenue North, Brooklyn Center, MN 55429 (US).

(21) International Application Number: PCT/US01/02929

(22) International Filing Date: 30 January 2001 (30.01.2001)

(74) Agents: LEWIS, Christopher, R.; Ratner & Prestia, 301 One Westlakes (Berwyn), P.O. Box 980, Valley Forge, PA 19482-0980 et al. (US).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/494,704 31 January 2000 (31.01.2000) US
09/677,905 3 October 2000 (03.10.2000) US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.


(71) Applicant: SCIMED LIFE SYSTEMS, INC. [US/US];
One SciMed Place, Maple Grove, MN 55311-1566 (US).

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,

(72) Inventors: CHOUINARD, Paul, F.; 9611 Polaris Lane North, Maple Grove, MN 55369 (US). PEIFFER, Dennis, A.; 9316 Wedgewood Lane North, Maple Grove, MN

[Continued on next page]

(54) Title: BRAIDED BRANCHING STENT, METHOD FOR TREATING A LUMEN THEREWITH, AND PROCESS FOR MANUFACTURE THEREOF



(57) Abstract: A bifurcated, braided stent has a body that branches into a plurality of legs and is adapted for deployment in a lumen. At least a portion of each leg of the stent comprises a discrete plurality of continuous filaments braided together, and at least a portion of the body comprises one or more of the continuous filaments from each of the legs braided together. The stent can be used for treating a diseased bifurcated lumen of the human being by deploying the stent therein. The stent can be constructed by a process comprising braiding each plurality of filaments to form the leg sections, and braiding one or more filaments from each plurality of filaments together to form the body. The process may be performed by creating the legs first and then the body, or vice versa. The stent may be constructed on a mandrel using a single braiding machine or multiple braiding machines.

WO 01/54621 A1

BEST AVAILABLE COPY



IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

**BRAIDED BRANCHING STENT, METHOD FOR TREATING A LUMEN
THEREWITH, AND PROCESS FOR MANUFACTURE THEREOF**

RELATED APPLICATIONS

The application claims priority based upon U.S. Patent Application No. 09/494,704, filed on January 31, 2000, and U.S. Patent Application No. 09/677,905, filed on October 3, 2000, and is related to U.S. Patent Application No. 09/494,980, filed on January 31, 2000, and the PCT Application (R&P docket number BSI-463WO) filed the same day as this application and claiming priority upon the '980 Application.

TECHNICAL FIELD

This invention relates generally to endoluminal stents, grafts, and/or prostheses and, more specifically, to braided stents adapted for deployment in branched lumina and processes for their manufacture.

BACKGROUND OF THE INVENTION

A stent is an elongated device used to support an intraluminal wall. In the case of a stenosis, a stent provides an unobstructed conduit for blood in the area of the stenosis. Such a stent may also have a prosthetic graft layer of fabric or covering lining the inside or outside thereof, such a covered stent being commonly referred to in the art as an intraluminal prosthesis, an endoluminal or endovascular graft (EVG), or a stent-graft.

A prosthesis may be used, for example, to treat a vascular aneurysm by removing the pressure on a weakened part of an artery so as to reduce the risk of rupture. Typically, a prosthesis is implanted in a blood vessel at the site of a stenosis or aneurysm endoluminally, i.e. by so-called "minimally invasive techniques" in which the prosthesis, restrained in a radially compressed configuration by a sheath or catheter, is delivered by a deployment system or "introducer" to the site where it is required. The introducer may enter the body through the patient's skin, or by a "cut down" technique in which the entry blood vessel is exposed by minor surgical means. When the introducer has been threaded into the body lumen to the prosthesis deployment location, the introducer is manipulated to cause the prosthesis to be ejected from the surrounding sheath or catheter in which it is restrained (or alternatively the surrounding sheath or catheter is retracted from the prosthesis), whereupon the prosthesis expands to a predetermined diameter at the deployment location, and the introducer is withdrawn. Stent expansion may be effected by spring elasticity, balloon expansion, or by the self-expansion of a thermally or stress-induced return of a memory material to a pre-conditioned expanded configuration.

Various types of stent architectures are known in the art, including many designs comprising a filament or number of filaments, such as a wire or wires, wound or braided into a

- 2 -

particular configuration. Included among these wire stent configurations are braided stents, such as is described in U.S. Patent No. 4,655,771 to Hans I. Wallsten and incorporated herein by reference, the '771 Wallsten patent being only one example of many variations of braided stents known in the art and thus not intended as a limitation of the invention described herein later.

- 5 Braided stents tend to be very flexible, having the ability to be placed in tortuous anatomy and still maintain patency. The flexibility of braided stents make them particularly well-suited for treating aneurysms in the aorta, where the lumen of the vessel often becomes contorted and irregular both before and after placement of the stent.

- Among the many applications for stent-grafts is for deployment in bifurcated lumen, such as for repair of abdominal aortic aneurysms (AAA). Various stent-graft configurations are known in the art for bifurcated applications, including single-piece and modular designs, graft designs fully supported by stents, and graft designs only partially supported by stents. Referring now to Figs. 1A and 1B, there are shown the components of a modular, non-braided, bifurcated, stent 10 for use with a fully-supported graft as is fully described in U.S. 5,609,627 to Goicoechea *et al* and adapted for implantation within the aorta of a human. By "fully-supported" it is meant that the graft is adapted to have stent structure underlying the graft throughout the entire length of the graft, as opposed to having extensive lengths of unsupported graft between anchoring stent portions, as will be described herein later.

- As shown in Fig. 1A, stent 10 comprises a main body 12 which bifurcates into a first frustoconical leg transition 14 with a dependent first leg 16, and a second frustoconical leg transition 18. Second leg 20 is a modular component comprising a frustoconical part 22 adapted to interlock within second leg transition 18, and a depending portion 24. Frustoconical part 22 may have barbs 23 to help firmly connect second leg 20 to leg transition 18. As shown in Fig. 2, such a bifurcated stent 10 is typically implanted within the vasculature such that the main body 12 and leg transitions 14 and 18 are positioned within the aorta main portion 26 and with the dependent first leg 16 and depending portion 24 of second leg 20 each positioned within respective iliac arteries 28 and 30. Modular designs are also available wherein both legs are modular components. All of the bifurcated stents described herein, regardless of underlying structure, generally resemble the configuration shown in Fig. 2 when fully implanted.

- As shown in Figs. 1A and 1B and as fully described in the '627 patent, the structure of stent 10 is a continuous wire zig-zag structure comprising a series of struts 32 joined at apices 34 and wound into hoops 36, with abutting hoops joined together in some manner, such as with sutures, at abutting apices. One potential disadvantage of zig-zag stent architecture is that the apices of the zig-zag structure can rub against the graft, causing wear in the graft.

Modular, fully-supported, bifurcated stent-graft designs using braided architecture are also known. Such designs typically comprise a tubular stent that is crimped or pinched together in the middle or at one end to form a septum and two smaller lumina. These two lumina can then be used as sockets for the iliac sections. The braided stents have the advantage of being
5 very adaptable to tortuous anatomy as compared to other stent architectures. The formation of the crimp, however, can cause metal cold-work and embrittlement in the stent wires and can result in bulkiness in the bifurcation region, requiring a relatively larger deployment profile than other designs.

To overcome the potential disadvantages of modular designs, it is also known to
10 provide one-piece or "unitary" stent designs. Such known designs may be fully supported or only partially supported, such as by having anchoring stent portions only located at the end sections adjacent each opening of the graft. One piece stent designs having a zig-zag stent architecture still have the same disadvantage of potential graft wear due to rubbing of the apices. One-piece graft designs that are only partially supported have the potential disadvantage that the
15 differences in radial strength and flexibility between the unsupported and supported regions makes the stent-grafts susceptible to kinking when navigating through tortuous lumina.

Thus, there is still a need in the art to provide a fully-stent-supported, bifurcated stent-graft that is flexible for navigation through tortuous lumina and that minimizes the risk of elements of the stent architecture creating wear in the graft covering or liner.

20 SUMMARY OF THE INVENTION

The invention comprises a branching stent for deployment in a lumen, the stent comprising a body that branches into a plurality of legs. At least a first leg portion of each leg comprises a discrete plurality of continuous filaments braided together and at least a first body portion of the body comprises at least one (preferably more, and more preferably all) of the
25 continuous filaments from each discrete plurality of continuous filaments braided together. At least one of the legs or the body may further comprise a second portion thereof having a non-braided stent architecture, or each of the legs and the body may further comprise a braided stent architecture throughout the entire respective lengths thereof. The stent may be a bifurcated stent having an interface between the body and the legs with an open crotch region between the legs at
30 the interface or a closed crotch region between the legs at the interface. A stent with a closed crotch may further comprise an open hip region.

The invention also comprises a stent for deployment in a lumen, the stent comprising a plurality of continuous filaments braided together, at least one filament comprising a tapered filament having at least one first region having a first, relatively-larger cross-sectional
35 area and at least one second region having a second, relatively-smaller cross-sectional area. A

- 4 -

braided stent having tapered wire according to the present invention may be a bifurcated stent or a non-bifurcated stent.

5 The invention also comprises a method for treating a diseased branched lumen of a human being, the branched lumen comprising a main section that branches into a plurality of branches. The method comprises the step of deploying within the branched lumen a branching
10 stent comprising a body that branches into a plurality of legs. At least a first leg portion of each leg comprises a discrete plurality of continuous filaments braided together, and at least a first body portion of the body comprises at least one of the continuous filaments from each discrete plurality of continuous filaments braided together. The deployment step comprises deploying the
10 body in the main section and deploying each leg within one of the branches.

The invention further comprises a process for constructing a braided, branched stent having a body and a plurality of legs, each leg comprising a discrete plurality of filaments, the process comprising the steps of: (a) braiding each plurality of filaments to individually form
15 at least first leg portions of each of the legs; and (b) braiding at least one filament from each plurality of continuous filaments together to form a first body portion of the body. Step (a) may
20 comprise the steps of: (i) braiding a first discrete plurality of filaments to form the first leg; and (ii) braiding a second discrete plurality of filaments to form the second leg, and step (b) may comprise braiding the first plurality of filaments and the second plurality of filaments together to form the body. Step (a) may be performed prior to step (b), or vice versa. The stent may be
20 braided around a mandrel having a mandrel body, a first detachable mandrel leg, and a second detachable mandrel leg. In such case, step (a)(i) comprises braiding the first plurality of filaments about the first detachable mandrel leg, step (a)(ii) comprises braiding the second plurality of filaments about the second detachable mandrel leg, and step (b) comprises braiding the first
25 plurality of filaments and second plurality of filaments together about the mandrel body.

25 The braiding may be performed on a braiding machine having a predetermined plurality of bobbin carriers adapted to revolve in a pattern about a longitudinal axis. A first set of bobbin carriers may be adapted to revolve in a first circumferential direction and a second set of bobbin carriers may be adapted to revolve in a second circumferential direction, each bobbin carrier adapted to carry at least one bobbin. Each bobbin is adapted to provide one or more
30 filaments for braiding within the stent. In such case, step (a)(i) comprises using filaments from a first portion of the predetermined plurality of bobbins to braid the first leg about the first detachable mandrel leg positioned substantially along the longitudinal axis in a braiding zone. The braiding zone is defined as a conical zone defined by the filaments extending from the bobbins to the stent on the mandrel. In step (a)(ii), the process comprises using filaments from a
35 second portion of the predetermined plurality of bobbins to braid the second leg about the second

detachable mandrel leg positioned in the braiding zone. Step (b) comprises using filaments from both portions of the predetermined plurality of bobbins to braid the body about the mandrel body positioned in the braiding zone.

Thus, the process may further comprise the steps of: (A) first performing step
5 (a)(i); (B) then removing the first portion of the predetermined plurality of bobbins from the braiding machine and removing the first mandrel leg from the braiding zone; (C) then performing step (a)(ii); (D) then returning the first portion of the predetermined plurality of bobbins to the braiding machine, attaching the first mandrel leg and the second mandrel leg to the mandrel body,
10 and positioning the mandrel body in the braiding zone; and (E) then performing step (b). The process may instead comprise the reverse: (A) first performing step (b); (B) then removing the second portion of the predetermined plurality of bobbins from the braiding machine and attaching the first mandrel leg to the mandrel body; (C) then performing step (a)(i); (D) then returning the second portion of the predetermined plurality of bobbins to the braiding machine and removing
15 the first portion of the predetermined plurality of bobbins from the braiding machine, attaching the second mandrel leg to the mandrel body, detaching the first mandrel leg from the mandrel body, and positioning the first leg of the stent outside the braiding zone so that the first leg does not interfere with performance of step (a)(ii); and (E) then performing step (a)(ii).

According to an alternative embodiment of the invention, a process for constructing a braided, branched stent having a body and a first and second leg, comprises:
20 braiding a first discrete set of filaments to form the first leg using a first braiding machine for accommodating at least a first number of bobbin carriers; braiding a second discrete set of filaments to form the second leg using either the first braiding machine or another braiding machine for accommodating at least a second number of bobbin carriers; and braiding the first and second sets of filaments together to form the body using another braiding machine for
25 accommodating at least a third number of bobbin carriers. The first and second numbers may be equal to one another and the third number may be equal to the first number plus the second number. The first, second, and third numbers may be less than a full bobbin carrier capacity of each respective braiding machine, such as the number which produces a 1:1 braiding ratio. Either the legs or body may be braided first, and a number of different braiding configurations
30 can be developed according to this embodiment.

BRIEF DESCRIPTION OF DRAWINGS

The invention is best understood from the following detailed description when read in connection with the accompanying drawing. It is emphasized that, according to common practice, some of the features of the drawing are not to scale. On the contrary, the dimensions of

- 6 -

some of the features are arbitrarily expanded or reduced for clarity. Included in the drawing are the following figures:

Fig. 1A is a front view of one stent component of an exemplary bifurcated intraluminal stent known in the art.

5 Fig. 1B is a front view of a mating stent component adapted to be connected to the bifurcated stent component of Fig. 1A.

Fig. 2 is a front view of the stent components shown in Fig. 1A and Fig. 1B in an assembled configuration implanted in the aortic region of a human, as is known in the art.

10 Fig. 3 is a front view of a portion of an exemplary stent embodiment having an open crotch according to the present invention.

Fig. 4A is a front view of an exemplary assembled modular mandrel in accordance with this invention.

Fig. 4B is a right side view of the assembled modular mandrel of Fig. 4A, showing hidden components (not shown in Fig. 4A) with dashed lines.

15 Fig. 4C is a bottom view of the trunk mandrel portion of the mandrel of fig. 4A.

Fig. 5A is a front view of the notch gears of a braiding machine, loaded with the first set of wire bobbins to form the first leg section of the braided stent about the first leg mandrel.

20 Fig. 5B is a front view of the notch gears in the braiding machine of Fig. 5A, with the first set of bobbins regrouped to the right side after forming the first leg section.

Fig. 5C is a front view of the notch gears in the braiding machine of Fig. 5A, with the second set of bobbins regrouped to the left side after forming the second leg section of the stent about the second leg mandrel.

25 Fig. 5D is a front view of the notch gears in the braiding machine of Fig. 5C, shown fully loaded with both the first set and second set of bobbins and both leg mandrels.

Fig. 5E is a front view of the notch gears in the braiding machine of Fig. 5D forming the braided trunk portion of the stent about the trunk mandrel that is connected to both leg mandrels.

30 Fig. 5F is a front view of the notch gears in the braiding machine of Fig. 5A in an alternative embodiment wherein the second set of bobbins is not regrouped to the left side prior to adding back in the first set of bobbins.

Fig. 6 is a side view of the notch gears in the braiding machine of Fig. 5A showing the conical configuration of the wires being braided about the mandrel.

35 Fig. 7 is a front view of a portion of the notch gears in the braiding machine of Fig. 5A and a front view of a rack for holding bobbins removed from the machine.

Fig. 8 is a front view of a portion of an exemplary stent embodiment having a closed crotch and open hips according to the present invention.

Fig. 9 is a front view illustration of an exemplary stent embodiment having legs in a 1:1 single filament braiding ratio and the body in a 1:1 paired filament braiding ratio according to the present invention.

Fig. 10A is a front view illustration of a portion of an exemplary stent embodiment having a closed crotch and closed hips according to the present invention.

Fig. 10B is a front view of an enlarged portion of the stent of Fig. 10A, showing interlocked filaments from each leg providing closure for the crotch.

Fig. 11A is a front view illustration of a portion of another exemplary stent embodiment having a closed crotch and closed hips according to the present invention.

Fig. 11B is a front view of an enlarged portion of the exemplary stent of Fig. 11A, showing a staple providing closure for the crotch.

Fig. 12 depicts an end portion of an exemplary stent embodiment having an atraumatic end winding, the stent having been cut longitudinally and flattened.

Fig. 13A depicts an end portion of an exemplary stent embodiment having continuous apices at the end of the stent as is known in the art, the stent having been cut longitudinally and flattened.

Fig. 13B depicts an end portion of an exemplary stent embodiment having ends that terminate freely at the end of the stent as is known in the art, the stent having been cut longitudinally and flattened.

Fig. 13C depicts an end portion of an exemplary stent embodiment having ends that terminate in a twisted configuration at the end of the stent as is known in the art, the stent having been cut longitudinally and flattened.

Fig. 13D depicts an end portion of an exemplary stent embodiment having ends that terminate in a non-braided configuration with continuous apices at the end of the stent, the stent having been cut longitudinally and flattened.

Fig. 14A depicts an exemplary side view of a male quick connect component that facilitates removal and replacement of the bobbin carrier in performing the method according to the present invention.

Fig. 14B depicts an exemplary plan view of a female quick connect component that facilitates removal and replacement of the bobbin carrier in performing the method according to the present invention.

Fig. 15A depicts a portion of an exemplary stent embodiment having a 1:1 single filament braiding ratio as is known in the art, the stent having been cut longitudinally and flattened.

Fig. 15B depicts a portion of an exemplary stent embodiment having a 2:2 single filament braiding ratio as is known in the art, the stent having been cut longitudinally and flattened.

Fig. 15C depicts a portion of an exemplary stent embodiment having a 1:1 paired filament braiding ratio as is known in the art, the stent having been cut longitudinally and flattened.

Fig. 16 is a front view of the notch gears of a braiding machine, loaded with a set of wire bobbins in 1:1-in-train configuration that produces a 1:1 paired filament braiding ratio, as is known in the art.

Fig. 17 is a cross-sectional view of an exemplary stent according to the present invention comprising tapered filaments.

Figs. 18A-D depict steps in an exemplary method for moving bobbins to a rack after braiding the right and left legs on a 24-carrier braider.

Figs. 19A-C depict steps in an exemplary method for moving bobbins from left and right semicircular racks onto a 48-carrier braider.

DETAILED DESCRIPTION OF INVENTION

The invention will next be illustrated with reference to the figures wherein similar numbers indicate the same elements in all figures. Such figures are intended to be illustrative rather than limiting and are included herewith to facilitate the explanation of the apparatus of the present invention.

Referring now to Fig. 3, there is shown a bifurcated, braided stent 50 according to the present invention. As shown in Fig. 3, the stent comprises a trunk section 52, a first iliac leg 54 and a second iliac leg 56. Stent 50 as shown in Fig. 3 is a unitary stent. That is, iliac legs 54 and 56 are continuous with trunk section 52, unlike modular stent designs in which two or more stent segments are assembled together to form the various parts of the stent (e.g., the trunk section and the two legs). As used herein, the term "unitary" means a stent having portions of each of its various parts made as a single unit. Thus, a unitary stent contemplates a stent whose entire length of all of its parts are made as a single unit, without the need to attach additional stent segments upon deployment. In addition, a unitary stent may be used in conjunction with stent segments, if it is desired to attach such segments to either the legs or the trunk section upon deployment.

It should be noted herein that unitary stent 50 as shown in Fig. 3 is merely one exemplary embodiment, and that this invention is applicable to "modular", braided stents as well. As used herein, the term "modular" means a stent having at least two discrete portions adapted for assembly in situ. As is well-known in the art, one type of exemplary modular bifurcated stent may include a trunk section that bifurcates into a single leg on one side adapted to extend into one iliac, and a socket on the other side, with the other leg being a modular piece adapted to be inserted into the socket, similar to the configuration shown in Figs. 1A and 1B. Another type of modular bifurcated stent may comprise only a trunk section with a bifurcated region that terminates in two short sockets into which two discrete leg members are adapted to be inserted. Although not depicted herein, such general configurations are well-known in the art, and when fully assembled, resemble the unitary configurations depicted in Figs. 3 and 8, except that there is an overlap region where each leg member is inserted into each socket as is well-known in the art. The term "leg" as used herein with respect to a stent having a body portion and leg portions may refer to a full, integral leg adapted to, for example, extending into an iliac artery, or may refer to a socket portion of a leg adapted to receive a modular leg element. Thus, although the invention as illustrated and described herein primarily references full leg structures, each of the methods and structures described herein is equally applicable to partial leg structures such as sockets for receiving modular leg elements.

Bifurcated region 53 as shown in Fig. 3, rather than being a crimped or pinched region, is formed by the weave of the stent filaments 58R and 58L. As can be seen in Fig. 3, a typical braided stent comprises a first set of filaments 58L wound in a first helical direction (to the left as shown in Fig. 3) and a second set of filaments 58R wound in a second, opposite helical direction (to the right as shown in Fig. 3), forming a plurality of overlaps 55. Filaments 58L and 58R may be wire, such as nitinol or stainless steel, or may comprise polymer or any type of filaments known in the art.

As used herein, a "braided" stent refers to a stent formed of at least two continuous filaments which are interwoven in a pattern, thus forming overlaps 55, as shown in Fig. 3. At each overlap, one filament is positioned radially outward relative to the other filament. Following each filament along its helical path through a series of consecutive overlaps, that filament may, for example be in the radial inward position in one overlap and in the radial outward position in a next overlap, or may in the inward position for two overlaps and in the outward position for the next two, and so on. As mentioned above, exemplary braided stents are disclosed in U.S. Patent No. 4,655,771 to Hans I. Wallsten. A typical braided stent is formed on a mandrel by a braiding or plaiting machine, such as a standard braiding machine known in the art and manufactured by Rotek of Ormond Beach, Florida. Any such braiding or plaiting

- 10 -

machine may be used, however, and the use of terminology specific to components of the machine manufactured by Rotek is not intended as a limitation to the use of that machine design. To the extent that the terminology used herein is specific to the components of any one or several machines, it should be understood such components specifically referred to herein generally have corresponding functionally equivalent components with respect to other machines. Thus, the scope of the method described and claimed herein for braiding the stent of present invention is not intended to be limited to the specific machine embodiment described herein, but extends to functionally equivalent machines also.

Braiding machines can be used for manufacturing the stent of the present invention about an exemplary modular mandrel as shown in Figs. 4A-C. Modular mandrel 60 as shown from the front in Fig. 4A and from the side in Fig. 4B, comprises a large diameter trunk section 62 and two, smaller diameter leg sections 64_L and 64_R. Leg sections 64 may comprise a male connector 66, as shown in Fig. 4B, which mates with a female receptacle 67 in trunk section 62 as shown in Figs. 4B and 4C. Hidden lines are not shown in Fig. 4A. Conversely, the female receptacle may be on leg sections 64_L and 64_R and the male connector on trunk section 62. Connector 66 and receptacle 68 may be threaded, may comprise slip fittings, or may otherwise enable leg sections 64_L and 64_R to be releasably connected trunk section 62. Tapered recess 69 serves to model the stent gradually to the different diameters of an aorta and iliac arteries.

Referring now to Figs. 5A-F, braiding machine 70 is shown schematically as typically comprising a number of notch gears 72 arranged in a circle. Machine 70 shown in Figs. 5A-F has twenty such notch gears 72, each notch gear adapted to rotate in the opposite direction as its neighboring notch gears, as illustrated by arrows A and B. This counter-rotation passes bobbin carriers 71, and the bobbins 74 mounted thereon, in a sinusoidal fashion from gear to gear, thus causing the bobbins to revolve about a longitudinal axis on which the circle is centered. The configuration of the notch gears, bobbin carriers, and bobbins to achieve this movement are well-known in the art, and an example of such a configuration is found in the braiding machine manufactured by Rotek.

Each bobbin comprises wire 75 wound thereon. The bobbin carrier and bobbin typically interface in a way that helps keep the wire unraveling from the bobbin under proper tension, as is known in the art. Although the motion of the bobbins is described herein, it should be understood that the bobbins 74 are moved by virtue of being mounted on bobbin carriers 71. Thus, although empty bobbin carriers 71 are shown in Fig. 5A, for example, each bobbin 74 also is mounted upon a bobbin carrier, creating a "loaded" bobbin carrier. To reduce clutter in Figs. 5A-5F, the underlying bobbin carrier is not shown for carriers loaded with bobbins 74. Bobbins 74L, shown in Fig. 5A with wire 75 unraveling from the left-hand side of the bobbin as viewed

facing the bobbin from outside of the circle of notch gears 72, travel sinusoidally around the circle of notch gears 72 in a counter-clockwise direction as viewed in Fig. 5A. Conversely, bobbins 74R with wire 75 unraveling from the right-hand side of the bobbin as viewed facing the bobbin from outside of the circle of notch gears 72, travel in a clockwise direction. Similarly,
5 bobbin carriers 71L travel counter-clockwise and carriers 71R travel clockwise.

The mandrel around which braided stent 50 is formed, such as leg mandrel 64R as shown in Fig. 5A, is moved in a controlled manner substantially along a longitudinal axis about which the circle of notch gears 72 is centered and about which the bobbin carriers 71 revolve. Thus, during processing, wires 75 extend from braiding machine 70 to mandrel 64 in a
10 conical configuration, as shown in Fig. 6. As can be seen from Fig. 6, as two bobbins cross one another, their respective filaments form an overlap such that the filament from the bobbin on the outer radius 76 is disposed radially outward (with respect to the axis of the stent being assembled) relative to the filament from the bobbin on the inner radius 78. The space contained within the cone formed by the wires extending between the bobbins and the mandrel and including the space
15 occupied by the mandrel is referred to herein as the "braiding zone" 90. Although the angles α_1 and α_2 of the wire to the mandrel may be varied as desired, α_1 and α_2 preferably each comprise an angle of approximately 55° when the braiding angle of a braided stent β is approximately 110° . This angle may vary dependent upon the exact radial position of the bobbin relative to the mandrel and whether the wire is on the inside radial position or outside radial position on an
20 overlap. Note, for example, that when bobbin 74L is positioned radially outwardly with respect to bobbin 74R on gear 72, angle α_1 is slightly larger than angle α_2 . As used herein, the phrase "substantially along the longitudinal axis" as used with respect to the alignment of the moving mandrel means that the mandrel does not have to be perfectly centered in the braiding zone, but merely needs to be aligned close enough to the longitudinal axis that the angles of the filaments
25 between the mandrel and the bobbins allows the braiding operation to create a functional braid without tangling the filaments.

Mandrel leg sections 64_L and 64_R may therefore each comprise a puller interface 68 for attaching a "puller" adapted to pull the mandrel away from the circle of notch gears 72 at a controlled rate as the braid is formed. For example, puller interface 68 may be a drilled and
30 tapped hole 68 in mandrel 64R as shown in Fig. 4B, and the puller may be a metal rod that has a threaded end or slip fitting adapted to be threaded or otherwise locked into the hole. The puller rod may be retracted away from the circle, for example, by a set of counter-rotating caterpillar tracks which hold the rod therebetween and move the rod in a controlled manner. Other types of pullers, methods of attachment of the puller to the mandrel, and means for moving the puller are

also acceptable, and the invention is in no way limited to the exemplary configuration provided herein. In alternative machine designs, a "pusher" may be provided at the opposite end rather than a puller. Any means for axially moving the mandrel through braiding zone 90 is acceptable.

The circle of notch gears 72 can be considered to have an outer radius 76 (on which bobbins 74R are positioned in Fig. 5A) and an inner radius 78 (on which bobbins 74L are positioned in Fig. 5A). In the half-full configuration shown in Fig. 5A, each bobbin 74L crosses over one bobbin 74R while on outer radius 76 before returning to inner radius 78 and crossing under another bobbin 74R. The braid created by such a weave can be said to have a 1:1 single filament braiding ratio (because each single filament crosses under another single filament, then over one, then under one, and so on). The 1:1 single filament braiding ratio is illustrated in Fig. 15A. During the cross-over step where a bobbin on outer radius 76 crosses over a bobbin on inner radius 78, the difference between angle α_1 and α_2 is sufficient to assure that the wires clear one another without tangling.

To form a braid around a mandrel, wires 75 extending from bobbins 74 can be secured to the end of the mandrel in almost any manner, such as by taping them or tying them, and do not even have to be kept in any particular orientation. For example, all the wires may all be taped or tied to a single point on one side of the mandrel. Once the braiding machine starts, it will stabilize into the proper braid configuration after only a few circumferential hoops of overlaps 55 (shown in Fig. 3) are formed. The portion between the proper configuration and the end can either be cut away as scrap or unbraided and then manipulated to form a non-braided end winding, as is discussed herein later. In the alternative, to minimize scrap, the ends of wires 75 may be wound around pins (not shown) or otherwise secured to the mandrel in a spaced circumferential configuration similar to the configuration of bobbins 74 in braiding machine 70.

In one method for creating the braided bifurcated structure of the present invention, the braiding machine is first loaded as shown in Fig. 5A with a first portion 73 of a predetermined number of bobbins 74. The predetermined number of bobbins may comprise the maximum capacity of the machine and first portion 73 may, for example, comprise half of the bobbin capacity of the machine. The braiding operation is then performed as described above to form a first leg section of the braided stent around a first leg mandrel, for example leg mandrel 64R (either 64L or 64R may be the first leg mandrel, in which case the other is the second leg mandrel). After braiding the first leg section about mandrel first leg section 64R, bobbins 74 of first portion 73 can be regrouped to one side (the right side as shown in Fig. 5B) of the circle of notch gears 72.

The method for moving the bobbins may be by any of a number of ways. For example, certain bobbin carriers may comprise closed eyelets through which the wire is threaded, in which case the entire bobbin carrier may be removed. Other bobbin carriers, such as those manufactured, for example, by the Wardwell Braiding Machine Company of Central Falls, RI, comprise open, curled guides resembling a "pigtail" such that the bobbins may be simply unlocked and lifted off of their respective bobbin carriers and the filament readily removed from the guide. It should be understood that as referred to herein, removing or replacing "the bobbins" on and off of the machine may comprise removing or replacing the bobbins only or the bobbins as still attached to the bobbin carriers. Where the entire bobbin carrier is removed, the bobbin carrier may be removed by simply removing any fasteners holding it in place, or to facilitate quicker removal and replacement, a quick-connect fitting can be used. The quick-connect fitting may comprise any number of means well-known in the art for providing an interlocking engagement of one element with another, such as a magnetic connection, a twist-and-lock connection, a spring-loaded ball in channel connection, a lever-controlled cam connection, or any connection known in the art. The configuration shown in Figs. 14A and 14B is provided merely to show one example of such a quick-connection device. Any quick connection device may be used, however, and the invention is by no means limited to the use of the configuration shown in Figs. 14A and 14B.

Exemplary quick disconnect comprises a male component 140 (shown in Fig. 14A) attached to bobbin carrier base 142 and a female component 141 (shown in Fig. 14B), typically attached to the bobbin carrier footplate (not shown) that rides along the notch gears (not shown) of the braiding machine (not shown). Male component 140 comprises a cylindrical post 144 and a cylindrical pin 145 inserted perpendicular to and through the post. A helical spring 146 extends about post 144 from pin 145 to bobbin carrier base 142. The bobbin carrier (not shown) typically attaches to male component 140 on the surface (not shown) of bobbin carrier base 142 opposite post 144. Female component 141 comprises a base 148 having therein a cavity 147 having an X-shaped entryway 149 adapted to accept the post and the pin in one of two orientations. To connect male component 140 to female component 141, post 144 and pin 145 are inserted in cavity 149 and spring 146 is compressed while the male component is turned 1/8 of a full revolution such that the pin is positioned in accordance with indent 150 shown in dashed outline in Fig. 14B. Thus, the spring 146 biases pin 145 against indent 150 in the cavity wall such that the post and pin cannot rotate unless the spring is compressed further. The X-shape of the entryway 149 allows male component 140 to either be inserted and turned to the right or inserted and turned to the left, depending upon which side of the X the pin is inserted into. To disconnect the components, then, male component 140 may merely be manipulated to compress

spring 146 and then turned $1/8$ of a revolution either to the left or the right so that the pin can exit the cavity through the X-shaped entryway. In an exemplary construction, base 148 of female component 141 may comprise a block of metal machined to create cavity 149 and indent 150 and then attached to the bobbin carrier footplate, such as with screws 151.

5 The bobbin regrouping process can be essentially understood by comparing Figs. 5A and 5B. Prior to bobbin regrouping, the bobbins are configured as shown in Fig. 5A, with pairs of bobbins I, II, III, and IV positioned relative to one another as shown. To regroup the bobbins, pair III remains in place, and the remaining bobbins are moved such that there are no empty bobbin carriers between pairs of loaded bobbin carriers in the loaded portion of the circle of notch gears 72, as shown in Fig. 5B. Thus, pairs I, II, and IV move from the positions shown in Fig. 5A to the positions shown in Fig. 5B.

 During the bobbin regrouping steps, it is desirable to preserve the clockwise or counter-clockwise rotation of each bobbin 74. Bobbin carriers 71L can be said to form a first set of bobbin carriers that traverse the circle of notch gears 72 in the counter-clockwise direction, whereas bobbin carriers 71R form a second set of bobbin carriers that traverse the circle in the clockwise direction. Thus, it may be desirable for bobbin 74L that rests on a bobbin carrier 71L before regrouping, to also reside on a bobbin carrier 71L after regrouping. Where the entire bobbin carrier is removed, it is desirable for the bobbin carrier to be replaced in a position where it travels in the same direction as it traveled prior to removal. Thus, for example when braiding with a 1:1 single filament braiding ratio in the legs and a 2:2 single filament braiding ratio (described herein later) in the trunk, bobbin 74 (or bobbin/bobbin carrier combination) on inner radius 78 may need to be switched with the bobbin (or bobbin/bobbin carrier combination) on outer radius 76 for every alternating pair of bobbins. Thus, for example, for pairs of bobbins I, II, III, and IV shown in Fig. 5A, where pair III stays in position and the remaining bobbins are regrouped together, pair III and pair I remain with bobbin 74L on outer radius 76 and bobbin 74R on inner radius 78, whereas pair II and pair IV switch bobbin 74L to inner radius 78 and bobbin 74R to outer radius 76. The counter rotation of the notch gears means that each notch gear 72 having a clockwise-rotating bobbin 74R on outer radius 76 has neighboring notch gears on either side with the clockwise-rotating bobbin on inner radius 78. In an alternate embodiment, bobbin carriers 71L (and therefore bobbins 74L) may travel clockwise instead of counter-clockwise, with carriers 71R and bobbins 74R travelling counter-clockwise. It may be preferable, however, for the tangent of the wire to the bobbin to be on the same side of the bobbin as on the mandrel so that the wire is wound on the same helical direction on the mandrel as it was on the bobbin. For example, as shown in Fig. 5A, the wire originating from bobbin 74R is tangent to the right side

- 15 -

of both the bobbin and mandrel 64R, and likewise the wire originating from bobbin 74L is tangent to the left side of both the bobbin and mandrel.

After regrouping of the bobbins is complete, first portion 73 of the predetermined number of bobbins 74 is removed and put aside, along with the completed leg braid still on leg mandrel 64R. Referring now to Fig. 7, to facilitate removing (and later replacing) first portion 73 of bobbins 74, the bobbins (or bobbin carriers) may be stored on a rack 80 so that the bobbins maintain the correct orientation and do not get tangled while they are set aside. The rack may take any form, from a configuration that mimics the configuration of the circle of notch gears 72 to a linear configuration wherein each place for holding a bobbin is easily identified with a corresponding position in the circle. For example, as shown in Fig. 7, the rack may comprise a 10-row by 2-column array, columns C_{76} and C_{78} corresponding to outer radius 76 and inner radius 78 of machine 70, respectively, and rows $R_i - R_x$ corresponding to pairs of bobbins $i - x$ on machine 70. Thus, the bobbin on outer radius 76 of pair i is placed on row R_i , column C_{76} of rack 80, the bobbin on inner radius 78 of pair x is placed on row R_x , column C_{78} , and so on.

A second leg is then braided about leg mandrel 64L with a second portion 77 of the predetermined number of bobbins 74 in the same manner as the first leg, except this time, after the leg has been braided, the second portion 77 is regrouped to the opposite side (the left side as shown in Fig. 5C) of the circle of notch gears 72. The first portion 73 of bobbins has a first discrete plurality of continuous filaments associated with it while the second portion 77 has a second discrete plurality of continuous filaments associated with it. Thus, each leg 54 and 56 is individually braided and comprises a discrete plurality of continuous filaments, such that each leg consists of filaments that are separate entities relative to the filaments of the other leg. After second portion 77 has been regrouped, first portion 73 is returned to the machine, and leg mandrel 64R and the braid thereon are positioned alongside the second leg mandrel 64L as shown in Fig. 5D. The two mandrels are then attached to trunk section mandrel 62 as shown in Fig. 5E. With first portion 73 returned to braiding machine 70, each bobbin carrier on the machine now has a bobbin mounted thereon. The braiding operation continues, now with all forty bobbins traversing the circle of notch gears 72 to create a braid around trunk section mandrel 62.

Although not shown, some of the filaments may be curtailed at the interface between the legs and the trunk portion, such that the trunk portion might consist of less than all of the filaments from the two portions 73 and 77. Conversely, the trunk portion may comprise more than all the filaments from the two portions 73 and 77. It is only necessary that at least one continuous filament from each discrete plurality of continuous filaments extend into the trunk portion, although it is preferred that at least half of each do so, and most preferred that all of them do so. Furthermore, portions 73 and 77 as illustrated herein each comprise half of the total

- 16 -

number of bobbins. It may be desirable in certain applications, however, for one leg to have more filaments in it than the other, such as if one leg has a greater diameter than the other. In such a case, portions 73 and 77 may be unequal.

A variation on the above method may eliminate the step of regrouping the bobbins to one side of the circle of notch gears 72 before removing first portion 73 of the predetermined number of bobbins 74. In such case, first portion 73 is merely removed from the circle without regrouping, such as in the position shown in Fig. 5A, and stored. After braiding the second leg, second portion 77 of the predetermined number of bobbins 74 is then left in a spaced configuration similar to that shown in Fig. 5F, and the first portion 73 is merely inserted to fill the gaps between the second portion 77. Trunk section mandrel 62 is then attached to leg mandrels 64L and 64R and the winding continues as described above. This method produces a stent such as is shown in Fig. 8.

By either method described above for winding about trunk section mandrel 62, the wires are wound in a 2:2 single filament braiding ratio with the machine at full capacity as shown in Fig. 5E. A 2:2 single filament braiding ratio is illustrated in Fig. 15B wherein, for example, following consecutive overlaps of single filament 152 wound in a first helical direction, the filament travels over two oppositely-wound filaments 153 and 154 at overlaps 155 and 156, respectively, and then travels under two filaments 157 and 158 at overlaps 159 and 160, respectively, and so on. This is true of each filament in the braid. Fig. 15A illustrates a 1:1 single filament braiding ratio, wherein following consecutive overlaps of filament 161 wound in a first helical direction, the single filament travels over one oppositely-wound filament 162 at overlap 163 and then travels under filament 164 at overlap 165, and so on.

Rather than winding a first leg, removing the bobbins, then winding a second leg, bringing back in the removed bobbins, and then winding the trunk section all on the same machine, a plurality of machines may be used. For example, a first machine may be used only for winding leg sections. After each leg section is wound on the first machine, the bobbins may then be removed such as onto a rack as described above, and ported to a second machine. The second machine may be used for combining together two or more pre-wound leg sections.

The stent may be manufactured using braiding machines having a different number of notch gears or using a different percentage of the capacity when winding, thus allowing preparation of stents having a 1:1 single filament braiding ratio throughout as described below, a 1:1 paired filament braiding ratio as shown in Fig. 15C and described below, or other configurations as desired. The exact winding configuration, however, is not intended as a limitation upon this invention. Furthermore, the illustrations in Figs. 15A-C are intended only to

depict the general braiding configurations of the filaments in relation to one another, and do not necessarily represent the actual number of filaments or the precise look of an actual stent.

Using braiding machines having a different number of notch gears for different steps in the manufacturing process allows customization of the braid pattern in different regions of the stent. For example, referring now to Figs. 18A-D and 19A-C, a 24-carrier braiding machine 180 having twelve notch gears 72 is used to braid left leg 64L in a 1:1 braiding ratio as shown in Fig. 18A, ending with the bobbins configured in bobbin pairs 184i-vi as shown. For the left leg, these bobbin pairs 184i-vi are then transferred to a semicircular rack 182L in the positions shown. Bobbins 74L on outer radius 76 of braiding machine 180 shown in Fig. 18A are placed on the outer radius R_{76} of rack 182L shown in Fig. 18B and bobbins 74R on inner radius 78 are placed on inner radius R_{78} of the rack. Braiding machine 180 may be separated from bobbin pairs 184i-vi and then used to braid a right leg 64R as shown in Fig. 18D.

Alternatively, a second 24-carrier braiding machine may be used to braid right leg 64R. In yet another alternative embodiment, a second braiding machine adapted to accommodate greater or less than 24 carriers may be used, and the number of bobbins loaded on the machine may be less than or greater than the number used to form left leg 64L. Thereafter, bobbin pairs 186i-vi are transferred to semicircular rack 182R as shown in Fig. 18C, in the same manner as bobbin pairs 184i-vi were transferred to rack 182L. It should be noted that rack 182R may merely be an identical rack or even the same rack as rack 182L, merely oriented differently before being loaded with bobbins. Rack 182R has an orientation relative to rack 182L rotated 180° , as shown in Figs. 18B and 18C.

It should also be noted that braiding machines 180 and 190 are adapted to accommodate more than the number of bobbin carriers actually shown loaded on the machines in Figs. 18A-19C, and, in fact are loaded at half of their full capacity to achieve a 1:1 braiding ratio throughout the stent. The method of using different braiding machines may incorporate a first machine to make a first leg, a second machine to make the second leg, and a third machine to make the body. Each machine may have a different full capacity of bobbins and each may have a different capacity as actually loaded to make the respective stent elements. Furthermore, the first machine may be identical to the second machine, but may merely be loaded at a different capacity to produce a leg with a different number of filaments than the leg formed on the second machine. Where the first leg comprises a first number of filaments, the second leg comprises a second number of filaments, and the body comprises a third number of filaments, the third number can be less than, greater than, or equal to the first number plus the second number.

- 18 -

Semicircular racks 182L and 182R are then brought together as shown in Fig. 19A to form a full circle surrounding 48-carrier braiding machine 190, which has twenty-four notch gears 72. The bobbin pairs 184i-vi and 186i-vi are then transferred to braiding machine 190 as shown in Fig. 19B. In an alternative embodiment, the bobbin pairs 184i-vi on rack 182L can be unloaded onto braiding machine 190 prior to creating leg 64R, and then the same rack 182L can be inverted to form rack 182R and used to transfer bobbin pairs 186i-vi to braiding machine 190. Trunk mandrel 62 is then attached to leg mandrels 64L and 64R and braiding of the trunk in a 1:1 ratio is commenced.

Although the method of using multiple machines having different numbers of carriers is a preferred method for creating a stent having a 1:1 braiding ratio throughout, the multi-machine method can be used to customize the braid pattern in any number of ways. For example, a multi-machine method may be used to provide a stent having a 2:2 ratio throughout, or a 2:2 ratio in the legs and a 1:1 configuration in the trunk, or any other suitable configuration.

A 1:1 paired filament braiding ratio can be achieved by positioning the bobbin carriers on the notch gears in such a way that the bobbins traveling in the same helical direction travel in pairs such that no bobbin traveling in the opposite direction crosses in-between the pairs. This particular bobbin carrier configuration for achieving a 1:1 paired filament braiding ratio may also be referred to as "1:1-in-train" configuration, referring to how the bobbin pair travel together as if linked in a train. Such a positioning is shown in Fig. 16, where bobbins 74L proceed about the circle counterclockwise and bobbins 74R proceed clockwise.

Referring now to Fig. 9, this method may be used, for example, to produce a stent 92 having a body section 52 with a 1:1 paired filament braiding ratio. The 1:1 paired filament braiding ratio is also shown in Fig. 15C. As shown in Fig. 15C, following a pair of filaments 166 and 167 wound in a first helical direction through consecutive overlaps, the pair travels together over a pair of oppositely-wound filaments 168 and 169 at overlap 170 and then travels under another pair of oppositely-wound filaments 171 and 172 at overlap 173.

In an alternative embodiment for achieving a 1:1 paired filament braiding ratio, each bobbin carrier 71 may be adapted to hold two bobbins. The body of the stent may be wound with the bobbins grouped two bobbins to a single carrier, whereas the legs are wound with the bobbins distributed with only a single bobbin per each occupied carrier. This configuration for winding the body appears similar to Fig. 5A or 5F from above, except that each bobbin as shown represents two bobbins 74 stacked one on top of another. The stacked configuration can be derived essentially by first grouping the bobbins as shown in Fig. 5D and then consolidating, for example, bobbin 74L₁ on top of 74L₂ and bobbin 74R₁ on top of 74R₂ and so on around the circle, so that the resulting configuration resembles the configuration in Fig. 5F but with two

bobbins stacked one on top of the other. The result is that each carrier in each set of carriers having a common direction of rotation having two bobbins thereon is surrounded on both sides by empty carriers, such as for example, carrier 74L having empty carriers 71L on either side as shown in Fig. 5F. Similarly, each pair of loaded carriers having two bobbins apiece has an empty carrier therebetween, such as for example, carriers 74R having empty carrier 71R therebetween as shown in Fig. 5F.

The braided bifurcated stent may also be constructed by processes that are essentially the reverse of those described above. By such processes, the braiding begins about trunk section mandrel 62 with the full capacity of bobbins as shown in Fig. 5E, and then one portion of the bobbins 74 are removed from the machine and set aside while one leg of the stent is braided about a leg mandrel using the remaining portion of the bobbins. For example, first portion 73 may be removed while second portion 77 forms a braid about mandrel 64L as shown in Fig. 5C. After the trunk section and one leg of the stent have been created with one portion of the bobbins, that portion is removed and the other portion is returned to the machine so that the other leg can be braided about the other leg mandrel. Thus, second portion 77 may be removed and first portion 73 replaced in the machine to form a braid about mandrel 64R as shown in Fig. 5B.

Similar to the process wherein the legs are braided first, the full set of bobbins can be split to make the legs such that all the bobbins on one portion are used for one leg and all the bobbins on the other portion are used for the other leg, such as is shown in Figs. 5B and 5C, or the bobbins used to braid one side and the bobbins used to braid the other side may comprise alternating pairs prior to being split, such as is shown in Figs. 5A and 5F. Because one leg must be braided first and then the other leg must be braided in a position parallel to that leg, leg mandrel 64 must be removed and the first-created leg bent back out of the path of braiding zone 90 during creation of the second-created leg. Similarly, during creation of the first-created leg, the set of bobbins 74 and wires 75 connected thereto for creation of the second-created leg and extending from the trunk section of the stent must be pulled into a position that does not interfere with the braiding of the first-created leg.

Referring to Figs. 18A-D and 19A-C, the multi-machine method may also be practiced in reverse with the trunk being wound first and then each individual leg. In such case, after winding the trunk, bobbin pairs 184i-vi are transferred from machine 190 to rack 182L and bobbin pairs 186i-vi are transferred from machine 180 to rack 184L. Then, before winding each leg, the respective bobbin pairs are transferred from the respective rack to carrier 180.

Depending on the method of grouping the bobbins when converting from braiding the legs to braiding the body, or vice versa, crotch region 93 of the stent may be open or closed.

The method wherein the bobbins are grouped such that the bobbins from one leg are grouped on one side of the machine and the bobbins from the other leg are grouped on the other side of the machine as shown in Fig. 5D, produces a stent with an open crotch 93 such as is shown in Fig.

3. An EVG constructed using a braided stent having an open crotch thus has an unsupported bifurcation septum. That is, the graft may not have underlying stent structure in the area where the graft bifurcates into the two legs. This may provide certain advantages, such as elimination of any graft-stent wear in that particular region, which is a region that may be subjected to more movement than other portions of the stent, and thus likely to provide more such wear in other designs.

10 The method wherein the bobbins from each leg are alternated with the bobbins from the other leg as described with respect to Fig. 5F, produces a stent with a closed, woven crotch 93 and open hips 95, such as are shown in Fig. 8. To provide a closed crotch for the design shown in Fig. 3, one or more filaments from the adjacent legs may be crossed in crotch region 93 as illustrated in the enlarged view in Fig. 10B. Other configurations for closing crotch
15 93 with crossing filaments may be provided, such as by switching bobbins from one carrier to another as desired to produce different degrees of interwinding. Referring now to Figs. 11A and 11B, it may be desirable to group certain of the braided filaments 58 together, in particular filaments from opposite legs in crotch region 93, using staples or sutures 96 to provide additional structure.

20 To provide increased radial strength at the ends of the braided stent of this invention or to counteract a known end-effect of braided stent architecture wherein the ends tend to have lesser radial strength than the intermediate portion of the stent, the ends may be flared as is well known in the art, or the ends may comprise a non-braided stent architecture such as is shown in Fig. 12. The structure and method for making a hexagonal non-braided architecture 97
25 with an overlapping zig-zag end winding 98 shown in Fig. 12 is disclosed fully in pending U.S. Patent Application Serial Number 09/442,165 by the common inventors Chouinard and Haverkost of this invention, filed on November 17, 1999, assigned to the common assignee, and incorporated herein by reference. Consistent with the disclosure in the '165 Application, a stent according to the present invention having a braided crotch region may have a non-braided
30 architecture in any portion of the stent other than in the crotch. For example, in one embodiment every region except the crotch region may have a non-braided architecture. Other embodiments may include non-braided architecture in any region of the stent where additional radial strength is desired, such as between two braided regions. Yet another embodiment may have a non-braided architecture at every end on both the distal (furthest from the position outside the lumen from
35 which the stent is introduced) and proximal (nearest to the position outside the lumen from which

- 21 -

the stent is introduced) ends of the stent, or on only selected ends of the stent, such as only on the upstream end or ends. The end architecture is not limited to the architecture shown and described above, but may comprise any number of configurations known in the art. If desired, a separate stent having greater radial strength may be deployed to overlap one or more of the ends, as is also known in the art.

Another method for developing a greater radial strength in one section of the stent relative to another comprises using a tapered wire to form the stent. For example, the wire can taper from a first, relatively smaller diameter or cross-sectional area used for braiding leg sections 54 and 56, for example, to a second, relatively larger diameter or cross-sectional area used for braiding body 52. Thus, body 52 may have a greater radial strength than otherwise provided by a single wire diameter throughout. The taper may also be reversed to provide greater radial strength in the legs, if desired. This tapering may also be applied to non-bifurcated, braided stent designs. The use of a continuous wire having regions of different cross-sectional area for providing variable stiffness in different regions of a stent is generally discussed in U.S.

Application Serial Number 09/442,192 to Zarbatany et al., incorporated herein by reference.

Tapered filaments may be used on any braided stent, not just on a bifurcated stent. All of the plurality of continuous filaments may be tapered filaments, or only a fraction of the filaments. In a non-bifurcated stent, one end portion of the braided stent may comprise the larger cross-section ends of all the tapered filaments and the other end portion of the stent may comprise the smaller cross-section ends of all the tapered filaments. As used herein in connection with the braided stent, the "end portion" may comprise only a short portion, such as a single row of overlaps that includes the end of the stent, or may include a larger portion, such as one half or more of the stent that includes the end. One example of such a non-bifurcated stent comprising tapered wire is shown in Fig. 17. Stent 175 comprises a distal end portion 176 and a proximal end portion 177. The distal end portion has a larger stent diameter D1 and the proximal end portion has a smaller stent diameter D2. In certain applications, it may be desirable for the larger diameter portion of the stent to comprise a larger diameter filament than the filament diameter in the smaller diameter portion. Thus, as shown, each filament may have a diameter d1 in the larger diameter portion of the stent and a smaller diameter d2 in the smaller diameter portion of the stent. Furthermore, both the stent and the wire may gradually taper, such that intermediate diameters D3 and d3 are present in the region between diameters D1 and D2. In other embodiments, the diameter of the wire may taper less gradually, such that the change in wire diameter along the stent is more in the nature of a step-change. In one exemplary embodiment, for example, D1 may equal about 24 mm and D2 may equal about 12 mm, with d1 equal to about

- 22 -

0.355 mm and d2 equal to about 0.255 mm. Any variety of dimensions may be used. In some applications D1 may equal D2, with only d1 and d2 being varied along the length of the stent.

The tapered-filament stent may comprise any combination of end windings or braiding ratios discussed herein or known in the art. The tapered-filament stent may be configured in any way desired for placement in a lumen, such as tapering from one end to the other as shown in Fig. 17, or with a smaller diameter in the middle than in the ends, or vice versa, or merely a single diameter throughout. All of the wires in the braided stent may be tapered, or only some fraction of the wires. The filament may have multiple tapers, such as from a larger diameter at one end, to a smaller diameter in the middle, to a larger diameter at the other end, or vice versa. The smaller diameter section of the filament may be positioned such that it coincides with a tortuous portion of a lumen requiring greater flexibility than other regions of the stent. Although described herein with reference to a larger or smaller diameter, the wire may have a non-round cross-section, in which case the wire may taper from a relatively larger cross-sectional area to a relatively smaller cross-sectional area.

The end architecture as shown in Fig. 12 can be described as "atraumatic" in the sense that there are no loose wire ends that may puncture or irritate (cause trauma to) the lumen wall after implantation. Other methods of providing atraumatic ends may also be used as are known in the art. In particular, the stent may comprise, rather than, for example, ten filaments wound onto ten bobbins, five continuous filaments each having a first end wound onto a first bobbin and a second end wound onto a second bobbin, thus still having ten bobbins in all. The filaments can be positioned on the braiding machine with the midpoint of the filament making a loop around, for example, a radially protruding pin secured in the mandrel, and the first and second bobbins positioned on bobbin carriers in positions consistent with the helical angle of the stent and the distance of the mandrel from the bobbin carriers. Thus, the first and second bobbins may be positioned at opposite ends of a radius of the circle of notch gears, or at opposite ends of some chord through the circle, depending on the exact configuration of the machine and desired helical angle of the stent. An exemplary process for providing a stent with such ends is described in publication WO 99/25271 to Burlakov et al. and is incorporated herein by reference.

Thus, using the method described above, one end of the stent has continuous-wire apices 99 such as are shown in Fig. 13A at one end. The filaments on the opposite ends may be freely terminating ends 100, such as are shown in Fig. 13B; twisted together ends 101, such as are shown in Fig. 13C and in publication WO 99/25271; or atraumatically disposed ends in a non-braided architecture, such as for example in positions 102 and 103 as shown in Fig. 12 and further discussed in U.S. Patent Application Serial Number 09/442,165. These are only examples, however, as the free ends may terminate in any way known in the art. Although one

- 23 -

end of a stent may have some combination of continuous-wire apices 99 and otherwise-terminated free ends 100, 101, or 102 and 103, the preferred embodiment comprises one end of the stent having only continuous-wire apices 99. It should also be understood that because the winding process proceeds from one end of the stent to the other, typically either the body end comprises continuous-wire apices 99 and the leg ends comprise otherwise-terminated free ends 100, 101, or 102 and 103, or the leg ends comprise all continuous-wire apices and the body end comprises all otherwise-terminated free ends. All or only some of the leg ends may comprise continuous-wire apices.

The above method for providing continuous-wire apices at one end may also be combined with the use of tapered wire as described herein. For example, a wire having multiple tapers with a relatively smaller diameter in a middle region of the wire and a relatively larger diameter in the opposite end regions, may be wound onto two bobbins. The relatively smaller diameter wire may be, for example, wound about a protruding pin at the midpoint of the wire, and the each leg region braided as described herein. The trunk region may then be braided as described herein, with the taper in the wire diameter located such that the trunk has a relatively larger diameter wire than each of the legs. The wire may comprise only the first diameter at the opposite ends and the second diameter in the middle, with a gradual taper between regions, or the wire may comprise a third diameter intermediate the end and middle diameters for use in the bifurcated region.

The use of continuous-wire apices at one end may be further combined with the configurations described in U.S. Patent Application Serial Number 09/442,165, wherein one or more regions of the stent may comprise a non-braided configuration. Thus, for example, the midpoint of a wire, such as a tapered wire, may be positioned at a non-braided end of a stent, creating continuous apices 104 such as are shown in Fig. 13D. The non-braided architecture may be created, for example, by winding the wire about pins on a mandrel as is well known in the art, and then once the non-braided section has been formed, braiding the remainder of the stent about the mandrel as described herein. The parallel wire sections 105 in the non-braided portion may be optionally welded together prior to braiding the remainder of the stent.

The above combinations may also be used with a non-bifurcated, braided stent. For example, a braided, non-bifurcated stent may comprise tapered filaments wherein the ends of the stent comprise larger cross-sectional area regions of the tapered filaments and the middle of the stent comprises the smaller cross-sectional area regions of the tapered filaments. Conversely, the smaller cross-sectional area regions may be on the ends and the larger cross-sectional area in the middle. As the larger cross-sectional area wire tends to provide greater stiffness or greater radial strength or both, the larger cross-sectional wire may be used in any region of the stent

- 24 -

desired to have increased stiffness and radial strength relative to the rest of the stent, or may be used in certain regions to counteract influences which otherwise would result in lesser stiffness or lesser radial strength in such regions. Atraumatic end windings, such as the continuous-wire apices described herein and with reference to Publication WO 99/25271 and the various configurations as described herein with reference to U.S. Patent Application Serial Number 09/442,165, may also be used in conjunction with tapered filaments in such braided, non-bifurcated stents. Such end windings may also be used in non-bifurcated stents without tapered filaments.

To deploy the stent of this invention, the stent is typically compressed into a radially compressed state into an introducer as is well-known in the art. The stent is then introduced to the lumen into which it is to be deployed, navigated through the lumen to a deployment location, typically a diseased artery such as the aorta, and then expanded to a radially expanded state in the deployment location as is known in the art. The deployment of a unitary stent of the present invention is thus deployed by a method similar to that used for any unitary bifurcated stent known in the art, and the deployment of a modular stent according to the present invention is thus deployed by a method similar to that used for any modular bifurcated stent known in the art.

Although bifurcated stent designs have been shown and described herein, the method of the present invention may be used for creating a stent that branches into any number of multiple lumen, so long as there are a sufficient number of bobbins available in the braiding machine to provide an adequate number of wires for braiding the branch sections. To the extent that existing braiding machines may not have a sufficient number of bobbins, machines with a greater number of bobbins may be designed without departing from the scope of this invention.

Although illustrated and described above with reference to certain specific embodiments, the present invention is nevertheless not intended to be limited to the details shown. Rather, various modifications may be made in the details within the scope and range of equivalents of the claims and without departing from the spirit of the invention.

What is claimed:

1 1. A branching stent for deployment in a lumen, the stent comprising a body
2 that branches into a plurality of legs, wherein at least a first leg portion of each leg comprises a
3 discrete plurality of continuous filaments braided together and at least a first body portion of the
4 body comprises at least one of said continuous filaments from each discrete plurality of
5 continuous filaments braided together.

1 2. The stent of claim 1 wherein at least one of said legs or said body further
2 comprises a second portion thereof having a non-braided stent architecture.

1 3. The stent of claim 1 wherein each of said legs and said body has a
2 respective length and each of said legs comprises said first leg portion along the entire length of
3 said legs and said body comprises said first body portion along the entire length of said body.

1 4. The stent of claim 1 wherein said plurality of legs comprises a first leg
2 and a second leg, the first leg portion of the first leg comprises a first discrete plurality of
3 continuous filaments braided together, the first leg portion of the second leg comprises a second
4 discrete plurality of continuous filaments braided together, and the first body portion comprises
5 the first plurality of continuous filaments braided together with the second plurality of continuous
6 filaments.

1 5. The stent of claim 4 further comprising an interface between the body and
2 the first and second legs, wherein said first and second plurality of continuous filaments define an
3 open crotch region between the first and second legs at the interface.

1 6. The stent of claim 4 further comprising an interface between the body and
2 the legs, wherein said first and second plurality of continuous filaments define a closed crotch
3 region between the first and second legs at the interface.

1 7. The stent of claim 6, wherein said first and second plurality of continuous
2 filaments define an open hip region between each leg and the body at the interface.

1 8. The stent of claim 6 wherein the closed crotch region comprises at least
2 one overlap where a filament in the first plurality of filaments crosses with at least one filament in
3 the second plurality of filaments.

1 9. The stent of claim 8 wherein the closed crotch region comprises two
2 overlapping filaments from the first plurality of filaments and the second plurality of filaments.

1 10. The stent of claim 1 wherein at least one set of two or more adjacent
2 filaments is grouped together in at least one location with one of: a suture or a staple.

1 11. The stent of claim 10 further comprising an interface between the body
2 and the legs, wherein said plurality of continuous filaments defines a closed crotch region
3 between the legs at the interface, wherein the adjacent filaments grouped together comprise at

least one filament from a first plurality of filaments of a first leg grouped together in the crotch region with at least one filament from a second plurality of filaments of a second leg.

12. The stent of claim 1 wherein the body has a first end and each leg has a second end, at least one of the ends comprising an end portion that is flared radially outward.

13. The stent of claim 2 wherein the body has a first end and the legs each have a second end, at least one of the ends comprising an end portion having a non-braided stent architecture.

14. The stent of claim 1 further comprising a biocompatible graft connected thereto as one of: an outer covering, an inner liner, or a combination thereof.

15. The stent of claim 1 wherein the filaments comprise wire.

16. The stent of claim 15 wherein the wire comprises one of: nitinol or stainless steel.

17. The stent of claim 1 wherein the filaments comprise at least one tapered filament comprising at least one first region having a first, relatively-larger cross-sectional area and at least one second region having a second, relatively-smaller cross-sectional area.

18. The stent of claim 17 wherein the tapered filament is configured such that the stent body comprises the first region having the first, relatively-larger cross-sectional area and each of the stent legs comprises one of the second regions having the second, relatively-smaller cross-sectional area.

19. The stent of claim 17 wherein the tapered filament is configured such that each of the stent legs comprises the first region having the first, relatively-larger cross-sectional area and the stent body comprises one of the second regions having the second, relatively-smaller cross-sectional area.

20. The stent of claim 1 wherein the stent extends between a body end and a plurality of leg ends and in which the filaments terminate at each of the ends.

21. The stent of claim 1 wherein the stent extends between a body end and a plurality of leg ends and in which each filament forms a continuous apex at one of: (a) the body end or (b) the plurality of leg ends.

22. The stent of claim 1 wherein the stent extends between a body end and a plurality of leg ends and in which each filament at one of: (a) the body end, or (b) the plurality of leg ends, terminates in an atraumatic termination structure.

23. The stent of claim 1 wherein the stent comprises a radially compressed configuration for introduction into the lumen and a radially expanded configuration for deployment within the lumen.

1 24. The stent of claim 23 wherein the stent is expandable between the radially
2 compressed configuration and the radially expanded configuration by one of: balloon expansion,
3 self-expansion via spring elasticity, or self-expansion via a thermally or stress-induced return of a
4 pre-conditioned memory material.

1 25. The stent of claim 4 wherein the stent is adapted for deployment within a
2 bifurcated region of an aorta where the aorta branches into first and second iliac arteries, the first
3 leg of the stent adapted to be deployed in the first iliac artery and the second leg of the stent
4 adapted to be deployed in the second iliac artery and the body of the stent adapted to be deployed
5 in the aorta.

1 26. The stent of claim 1 wherein each leg comprises a 1:1 single filament
2 braiding ratio.

1 27. The stent of claim 4 wherein each leg comprises a 1:1 single filament
2 braiding ratio and the body comprises a 2:2 single filament braiding ratio.

1 28. The stent of claim 4 wherein each leg comprises a 1:1 single filament
2 braiding ratio and the body comprises a 1:1 paired filament braiding ratio.

1 29. The stent of claim 1 wherein the stent comprises a unitary stent having at
2 least two legs integrally attached to the body, each leg adapted for at least partial insertion into a
3 branch of said lumen.

1 30. The stent of claim 1 wherein the stent comprises a modular stent and
2 wherein at least one leg comprises a socket portion for receiving a modular leg element.

1 31. A process for constructing a braided, branched stent having a body and a
2 plurality of legs, each leg comprising a discrete plurality of filaments, the process comprising the
3 steps of:

4 a) braiding each plurality of filaments to individually form at least first leg
5 portions of each of the legs; and

6 b) braiding at least one filament from each plurality of continuous filaments
7 together to form a first body portion of the body.

1 32. The process of claim 31 wherein each leg and the body have respective
2 lengths and the process further comprises braiding the plurality of filaments in each leg over the
3 entire length of each leg and braiding all of the filaments of each plurality of leg filaments
4 together in the body over the entire length of the body.

1 33. The process of claim 31 further comprising one of: configuring at least a
2 fraction of one plurality of leg filaments into a non-braided configuration in a second portion of
3 the leg, configuring at least a fraction of each plurality of leg filaments into a non-braided
4 configuration in a second portion of the body, or a combination thereof.

1 34. The process of claim 31 wherein the plurality of legs comprises a first leg
2 and a second leg and step (a) comprises the steps of:

- 3 i) braiding a first discrete plurality of filaments to form the first leg; and
4 ii) braiding a second discrete plurality of filaments to form the second leg;

5 and

6 step (b) comprises braiding the first plurality of filaments and the second plurality
7 of filaments together to form the body.

1 35. The process of claim 34 wherein step (a) is performed prior to step (b).

1 36. The process of claim 34 wherein step (b) is performed prior to step (a).

1 37. The process of claim 34 comprising braiding the stent around a mandrel
2 having a mandrel body, a first detachable mandrel leg, and a second detachable mandrel leg,
3 wherein step (a)(i) comprises braiding the first plurality of filaments about the first detachable
4 mandrel leg, step (a)(ii) comprises braiding the second plurality of filaments about the second
5 detachable mandrel leg, and step (b) comprises braiding the first plurality of filaments and second
6 plurality of filaments together about the mandrel body.

1 38. The process of claim 34 comprising performing the braiding on a braiding
2 machine having a predetermined plurality of bobbins adapted to revolve in a pattern about a
3 longitudinal axis, a first set of bobbins adapted to revolve in a first circumferential direction and a
4 second set of bobbins adapted to revolve in a second circumferential direction, each bobbin
5 mounted upon a bobbin carrier adapted to carry at least one bobbin, each bobbin adapted to
6 provide one or more filaments for braiding within the stent, step (a) comprising in step (i) using
7 filaments from a first portion of the predetermined plurality of bobbins to braid the first leg about
8 the first detachable mandrel leg positioned substantially along the longitudinal axis in a braiding
9 zone, the braiding zone being a conical zone defined by the filaments extending from the bobbins
10 to the stent on the mandrel, and in step (ii) using filaments from a second portion of the
11 predetermined plurality of bobbins to braid the second leg about the second detachable mandrel
12 leg positioned in the braiding zone; and step (b) comprising using filaments from both portions of
13 the predetermined plurality of bobbins to braid the body about the mandrel body positioned in the
14 braiding zone.

1 39. The process of claim 38 further comprising the steps of:

2 A) first performing step (a)(i);

3 B) then removing the first portion of the predetermined plurality of bobbins
4 from the braiding machine and removing the first mandrel leg from the braiding zone;

5 C) then performing step (a)(ii);

6 D) then returning the first portion of the predetermined plurality of bobbins
7 to the braiding machine, attaching the first mandrel leg and the second mandrel leg to the mandrel
8 body, and positioning the mandrel body in the braiding zone; and

9 E) then performing step (b).

1 40. The process of claim 39 wherein prior to removing the first portion of the
2 predetermined plurality of bobbins from the machine, the process further comprises grouping the
3 first portion of the predetermined plurality of bobbins on a first side of the machine; and prior to
4 returning the first portion of the predetermined plurality of bobbins to the first side of the
5 machine, the process further comprises grouping the second portion of the predetermined
6 plurality of bobbins onto a second side of the machine.

1 41. The process of claim 40 wherein after or during the step of returning the
2 first portion of the predetermined plurality of bobbins to the machine in step D, the process
3 further comprises the steps of:

4 D1) identifying at least one adjacent pair of bobbins comprising a first bobbin
5 from the first portion of the predetermined plurality of bobbins and a second bobbin from the
6 second portion of the predetermined plurality of bobbins; and

7 D2) crossing the filaments attached to the first and second bobbins so that the
8 first leg and the second leg of the stent are interlocked together by the crossed filaments.

1 42. The process of claim 39 wherein the step of returning the first portion of
2 the predetermined plurality of bobbins to the machine in step D comprises placing each bobbin
3 from the first portion of the predetermined plurality of bobbins in a position located
4 circumferentially between two bobbins from the second portion of the predetermined plurality of
5 bobbins.

1 43. The process of claim 38 comprising the steps of:

2 A) first performing step (b);

3 B) then removing the second portion of the predetermined plurality of
4 bobbins from the machine and attaching the first mandrel leg to the mandrel body;

5 C) then performing step (a)(i);

6 D) then returning the second portion of the predetermined plurality of
7 bobbins to the machine and removing the first portion of the predetermined plurality of bobbins
8 from the machine, attaching the second mandrel leg to the mandrel body, detaching the first
9 mandrel leg from the mandrel body, and positioning the first leg of the stent outside the braiding
10 zone so that the first leg does not interfere with performance of step (a)(ii); and

11 E) then performing step (a)(ii).

1 44. The process of claim 43 comprising designating the second portion of the
2 predetermined plurality of bobbins to be removed from the machine in step B as all of the bobbins
3 on one side of the machine.

1 45. The process of claim 44 wherein prior to removing the second portion of
2 the predetermined plurality of bobbins in step B, the process further comprises the steps of:

3 B1) identifying at least one adjacent pair of bobbins comprising a first bobbin
4 from the first portion of the predetermined plurality of bobbins and a second bobbin from the
5 second portion of the predetermined plurality of bobbins; and

6 B2) crossing the filaments attached to the first and second bobbins so that the
7 first leg and the second leg of the stent are interlocked together by the crossed filaments.

1 46. The process of claim 44 comprising designating the first and second
2 portions of the predetermined plurality of bobbins as alternating bobbins of each set of bobbin
3 carriers such that in each set, each bobbin from the first portion is positioned on a bobbin carrier
4 circumferentially between two bobbins from the second portion at a step in the process
5 immediately prior to removal of the second portion from the machine in step B.

1 47. The process of claim 38 wherein:
2 the first set of bobbin carriers revolves about a longitudinal axis in a clockwise
3 circumferential direction,

4 the second set of bobbin carriers revolves about the longitudinal axis in a
5 counterclockwise circumferential direction, and

6 the braiding process in step (a) comprises braiding each leg in a 1:1 single
7 filament braiding ratio and configuring each of the first set of bobbin carriers and second set of
8 bobbin carriers with bobbins spaced one bobbin per every other carrier such that each carrier
9 having a bobbin thereon is positioned circumferentially between two empty carriers in that set of
10 bobbin carriers.

1 48. The process of claim 47 wherein the braiding process in step (b)
2 comprises braiding the body in a 2:2 single filament braiding ratio and configuring both the first
3 set of bobbin carriers and the second set of bobbin carriers with a single bobbin on every carrier.

1 49. The process of claim 47 wherein the braiding process in step (b)
2 comprises braiding the body in a 1:1-paired filament braiding ratio.

1 50. The process of claim 49 further comprising configuring the first set of
2 bobbin carriers and the second set of bobbin carriers in a 1:1-in-train configuration.

1 51. The process of claim 31 comprising braiding the stent using at least one
2 tapered filament comprising at least one first region having a first, relatively-larger cross-

- 31 -

sectional area and at least one second region having a second, relatively-smaller cross-sectional area.

52. The process of claim 51 comprising braiding each braided portion of each leg using one of the second regions of the tapered filament and braiding the braided portion of the body using the first region of the tapered filament.

53. The process of claim 51 comprising braiding each braided portion of each leg using one of the first regions of the tapered filament and braiding the braided portion of the body using the second region of the tapered filament.

54. The process of claim 38 comprising prior to steps (a) and (b), winding the filaments between two bobbins such that a first end of the filament is wound on a first bobbin and a second end of the filament is wound on a second bobbin, and positioning a midpoint of the filament on the mandrel to form an apex at an end of the stent.

55. The process of claim 51 comprising prior to steps (a) and (b), winding each tapered filaments between two bobbins such that a first end of the filament is wound on a first bobbin and a second end of the filament is wound on a second bobbin, and positioning a midpoint of the filament on the mandrel to form an apex at an end of the stent.

56. The process of claim 55 wherein the first end is located within one of the second regions having the second, relatively-smaller cross-sectional area and the second end is located within another of the second regions and the midpoint of the filament is located within the first region having the first, relatively-larger cross-sectional area.

57. The process of claim 55 wherein the first end is located within one of the first regions having the first, relatively-larger cross-sectional area and the second end is located within another of the first regions and the midpoint of the filament is located within the second region having the second, relatively-smaller cross-sectional area.

58. The process of claim 31 wherein step (a) is performed on a first braiding machine and step (b) is performed on a second braiding machine.

59. A multi-section stent comprising at least one braided section, which comprises a cylindrical mesh of a first set of filaments, and at least one non-braided, wound end section, which is connected to said braided section and comprises a second set of one or more filaments in a repeating configuration having at least one bent portion, wherein at least one continuous filament is contained in both the first and second sections and forms a continuous apex in the wound end section.

60. A process for constructing a braided, branched stent having a body and a first and second leg, each of said first and second legs comprising a discrete plurality of filaments, the process comprising the steps of:

4 (a) braiding a first discrete plurality of filaments to form the first leg using a
5 first braiding machine for accommodating at least a first number of bobbin carriers;

6 (b) braiding a second discrete plurality of filaments to form the second leg
7 using said first braiding machine; and

8 (c) braiding the first plurality of filaments and the second plurality of
9 filaments together to form the body using a second braiding machine for accommodating at least a
10 second number of bobbin carriers that is different from said first number.

1 61. The process of claim 60, wherein each bobbin carrier is adapted to hold a
2 bobbin having a filament wound thereon, a first plurality of bobbins is used in step (a), and a
3 second plurality of bobbins equal in number to the first plurality is used in step (b), the process
4 further comprising: performing steps (a) and (b) before step (c); after step (a) transferring the first
5 plurality of bobbins to a first bobbin rack; after step (b) transferring the second plurality of
6 bobbins to a second bobbin rack; and prior to step (c) transferring the first and second plurality of
7 bobbins from the first and second bobbin racks onto the second braiding machine.

1 62. The process of claim 61, wherein said first rack and said second rack are
2 semicircular and, prior to step (c), said first rack and said second rack are joined to form a
3 circular rack.

1 63. The process of claim 60, wherein each bobbin carrier is adapted to hold a
2 bobbin having a filament wound thereon, a first plurality of bobbins is used in step (a), and a
3 second plurality of bobbins equal in number to the first plurality is used in step (b), the process
4 further comprising: performing steps (a) and (b) before step (c); after step (a) transferring the first
5 plurality of bobbins to a first bobbin rack in a first orientation and then to the second braiding
6 machine; after step (b) transferring the second plurality of bobbins to the first bobbin rack in a
7 second orientation and then to the second braiding machine.

1 64. The process of claim 60, wherein each bobbin carrier is adapted to hold a
2 bobbin having a filament wound thereon, a first plurality of bobbins is used in step (a), and a
3 second plurality of bobbins equal in number to the first plurality is used in step (b), the process
4 further comprises: performing step (c) before steps (a) and (b); after step (c) transferring the first
5 plurality of bobbins from the second machine to a first bobbin rack and transferring the second
6 plurality of bobbins from the second machine to a second bobbin rack; prior to step (a)
7 transferring the first plurality of bobbins from the first rack onto the first braiding machine; and
8 prior to step (b) transferring the second plurality of bobbins from the second rack onto the first
9 braiding machine.

1 65. The process of claim 60 wherein the first number is less than a full
2 capacity of the first braiding machine and the second number is less than a full capacity of the
3 second braiding machine.

1 66. The process of claim 60 wherein each of the first number and the second
2 number are equivalent to a capacity of the respective braiding machine that produces a 1:1
3 braiding ratio.

1 67. A process for constructing a braided, branched stent having a body and a
2 first and second leg, each of said first and second legs comprising a discrete plurality of
3 filaments, the process comprising the steps of:

4 (a) braiding a first discrete plurality of filaments to form the first leg using a
5 first braiding machine for accommodating at least a first number of bobbin carriers;

6 (b) braiding a second discrete plurality of filaments to form the second leg
7 using a second braiding machine for accommodating at least a second number of bobbin carriers;
8 and

9 (c) braiding the first plurality of filaments and the second plurality of
10 filaments together to form the body using a third braiding machine for accommodating at least a
11 third number of bobbin carriers that is different from said first and second numbers.

1 68. The stent of claim 4 wherein each leg comprises a 1:1 single filament
2 braiding ratio and the body comprises a 1:1 single filament braiding ratio.




FIG. 1A
(Prior Art)




FIG. 1B
(Prior Art)

2/15




FIG. 2
(Prior Art)




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 5F




FIG. 6




FIG. 7

8/15




FIG. 8

9/15




FIG. 9




FIG. 10A




FIG. 11A




FIG. 10B




FIG. 11B




FIG. 13B
(Prior Art)




FIG. 13A
(Prior Art)




FIG. 12




FIG. 13D
(Prior Art)




FIG. 13C
(Prior Art)

11/15




FIG. 14A




FIG. 14B




FIG. 15A
(Prior Art)




FIG. 15B
(Prior Art)




FIG. 15C
(Prior Art)




FIG. 16
(Prior Art)




FIG. 17

14/15




FIG. 18A




FIG. 18B




FIG. 18C




FIG. 18D

15/15

FIG. 19A




FIG. 19B





FIG. 19C



A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61F2/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61F D04C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X	WO 00 44309 A (UNIV TEXAS) 3 August 2000 (2000-08-03)	1, 3, 4, 6, 15, 16, 20-28, 31, 32, 34-38, 60, 68
A	figures 1A, 4, 7-10, 11, 25A-28, 30, 31-33, 35-37, 40 page 12, line 17 - line 24 page 13, line 5 - line 12 page 16, line 9 - page 17, line 6 page 19, line 3 - line 15 page 22, line 1 - page 29, line 11	59, 67
	— -/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *Z* document member of the same patent family

Date of the actual completion of the international search

14 May 2001

Date of mailing of the international search report

30/05/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Mary, C

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 741 325 A (CHAIKOF ELLIOT L ET AL) 21 April 1998 (1998-04-21) figure 6 column 6, line 48 -column 7, line 26	1
A		31,59, 60,67
A	WO 98 19630 A (VASCULAR SCIENCE INC) 14 May 1998 (1998-05-14) figures 9-12 page 12, line 23 -page 13, line 20	1,31,59, 60,67
A	US 5 485 774 A (OSBORNE ROBERT) 23 January 1996 (1996-01-23) figure 1 column 2, line 30 - line 67	1,31,59, 60,67
A	WO 99 55256 A (INTRATHERAPEUTICS INC) 4 November 1999 (1999-11-04) page 6, line 28 -page 8, line 4	1-68
A	US 5 741 333 A (FRID NOUREDDINE) 21 April 1998 (1998-04-21) figures 4,5 column 6, line 3 -column 7, line 6	1-68

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0044309	A	03-08-2000	AU 3220100 A	18-08-2000
US 5741325	A	21-04-1998	AU 8012394 A	01-05-1995
			WO 9509586 A	13-04-1995
WO 9819630	A	14-05-1998	US 5976178 A	02-11-1999
			US 6036702 A	14-03-2000
			US 5972017 A	26-10-1999
			AU 5102198 A	29-05-1998
			AU 5105798 A	29-05-1998
			AU 5162598 A	29-05-1998
			AU 5162698 A	29-05-1998
			AU 5166498 A	29-05-1998
			AU 5168398 A	29-05-1998
			AU 5179698 A	29-05-1998
			AU 5197098 A	29-05-1998
			AU 5251498 A	29-05-1998
			AU 7000498 A	29-05-1998
			EP 0951251 A	27-10-1999
			EP 0951252 A	27-10-1999
			EP 0996386 A	03-05-2000
			EP 0949889 A	20-10-1999
			JP 2001502588 T	27-02-2001
			WO 9819629 A	14-05-1998
			WO 9819618 A	14-05-1998
			WO 9819631 A	14-05-1998
			WO 9819632 A	14-05-1998
			WO 9819732 A	14-05-1998
			WO 9819634 A	14-05-1998
			WO 9819608 A	14-05-1998
			WO 9819635 A	14-05-1998
			WO 9819636 A	14-05-1998
			US 6206912 B	27-03-2001
			US 5931842 A	03-08-1999
			US 6152945 A	28-11-2000
US 5485774	A	23-01-1996	CA 2124528 A	01-02-1995
WO 9955256	A	04-11-1999	AU 3766499 A	16-11-1999
US 5741333	A	21-04-1998	BE 1009278 A	07-01-1997
			CA 2173664 A	13-10-1996
			EP 0740928 A	06-11-1996

THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)